



COLD EXPANSION CRIMP RINGS F1960

SUBMITTAL DATA

PROJECT

Job Name: _____ Submitted by: _____ Date: _____
 Location: _____ Approved by: _____ Date: _____
 Engineer: _____ Order No.: _____ Date: _____
 Contractor: _____ Notes: _____
 Sales Rep.: _____

#CPR12 Quantity: _____
 #CPR58 Quantity: _____
 #CPR34 Quantity: _____



DESCRIPTION

PEX-a expansion rings with stop for use with Cold Expansion Fittings F1960.

TECHNICAL SPECIFICATIONS

Material: Crosslinked polyethylene (PEX-A)
Maximum temperature: 200°F (93.3°C)

Model#	Conn.	A		OD		ID		Weight	
		in	mm	in	mm	in	mm	lb	g
CPR12	½"	0.66	16.7	0.88	22.3	0.62	15.7	0.0044	2
CPR58	⅝"	0.78	19.8	1.00	25.4	0.75	19.0	0.0066	3
CPR34	¾"	0.88	22.4	1.13	28.7	0.87	22.1	0.0088	4.5



Standards

ASTM F877
ASTM F1960

NSF-PW
CSA B-137.5
NSF/ANSI 14

WARRANTY

Calefactio Solutions Inc. offers a one-year limited warranty from the date of purchase. The warranty is only valid if the product is installed and used under normal working conditions and for the purpose it was intended.

Quebec, Canada
T (450) 951-0818
F (450) 951-2165

CALEFACTIO RADIANT.COM