


PRODUCT CATALOG
Residential • Commercial
2024



RADIANT HEATING SYSTEM DESIGN SERVICE

Short on time and resources to design your radiant floor or snow melting project? The Calefactio team can help you every step of the way.

We offer fast turnkey service to help you execute your residential and commercial projects across Canada. With the guidance of our dedicated professionals, you'll be amazed how much you can get done in a short time.

ADVANTAGES

- We'll send you a customized looping plan and a product list faster than our competition.
- Our team of professionals will be there to offer support and answer your questions at all times.
- Our expertise and knowledge will help you choose the right components for your mechanical room.
- You'll save time and money.

OUR TEAM OF EXPERTS

Specialized technicians

Engineers

Designers

Over 25 years of experience in the field

WHY CHOOSE CALEFACTIO?

- Our solutions are developed locally here in Canada.
- We offer reliable, high-performance products and provide no-pressure support services.
- We do things differently, which motivates us to go the extra mile.

OUR ACHIEVEMENTS




To complete a design request, scan the QR code.



PEX-A TUBING

Calpex-R

Calefactio reticulated polyethylene tubing's (PEX-a) are built with an anti-oxygen barrier that limits oxygen diffusion in the system to protect its components



STANDARDS

ASTM F876 • ASTM F2023 • ASTM F877 • CSA B137.5
ULC S102.2 • ASTM E84 • DIN 4726 • PEX5106 • NSF14/61

LISTING

cNSFus-rfh • CSA • ICC-ES • Intertek

Model#	Description	Weight	
		lb	kg
CALPEX-R-12-300A	PEX-a 1/2" 300 ft	18	8.1
CALPEX-R-12-500A	PEX-a 1/2" 500 ft	30	13.4
CALPEX-R-12-1000A	PEX-a 1/2" 1000 ft	59	26.8
CALPEX-R-58-300A	PEX-a 5/8" 300 ft	14.5	10.9
CALPEX-R-58-400A	PEX-a 5/8" 400 ft	32	14.5
CALPEX-R-58-500A	PEX-a 5/8" 500 ft	40	18.1
CALPEX-R-58-1000A	PEX-a 5/8" 1000 ft	80	36.3
CALPEX-R-34-100A	PEX-a 3/4" 100 ft	11	5
CALPEX-R-34-300A	PEX-a 3/4" 300 ft	35	15.9
CALPEX-R-34-400A	PEX-a 3/4" 400 ft	44	20
CALPEX-R-34-500A	PEX-a 3/4" 500 ft	55	25
CALPEX-R-34-1000A	PEX-a 3/4" 1000 ft	110	50
CALPEX-R-1-100A	PEX-a 1" 100 ft	17.9	8.1
CALPEX-R-114-100A	PEX-a 1 1/4" 100 ft	25.3	11.5
CALPEX-R-112-100A	PEX-a 1 1/2" 100 ft	35	15.9
CALPEX-R-2-100A	PEX-a 2" 100 ft	60	27.2

STRAIGHT LENGTH


Model#	Description	Weight	
		lb	kg
CALPEX-R-1-20AS	PEX-a 1" 20 ft	3.5	1.59
CALPEX-R-114-20AS	PEX-a 1 1/4" 20 ft	5.25	2.38
CALPEX-R-112-20AS	PEX-a 1 1/2" 20 ft	7.3	3.3
CALPEX-R-2-20AS	PEX-a 2" 20 ft	11.9	5.4

CALPEX-R tubing is extremely flexible and durable, so you can create tight crimping angles by simply applying minimal pressure.

MANIFOLD


Caltherm Pro

Our stainless steel manifold kit comes with 1 in connection.




TECHNICAL DATA

- Headers with 1" connection
- Made of 304 stainless steel
- Pre-assembled on wall support for easy installation
- Integrated flowmeters (5 LPM / 1.5 GPM per loop)
- Maximum pressure: 125 psi / 862 kPa
- Maximum temperature: 230°F / 110°C
- Provided with air purger and drain
- Compatible with Calefactio 24 volt actuator (#AC24NC)
- Compatible with ethylene and propylene glycol up to a maximum of 50% concentration
- Possibility to isolate each loop with isolating valve and balancing valve
- 2-way NPT ball valve with integrated thermometer



Headers are offered in 14 models (2 to 15 loops) with a maximum flow rate of 22.5 gallons per minute (GPM).

The integrated flowmeters allow the user to adjust the flow easily in each loop. Circuit isolation valves are also compatible with 24V actuators from Calefactio (#AC24VNC).



#Model	Loops	Maximum Flow		Length (A)		Weight	
		LPM	GPM	in	mm	lb	kg
MAN2-SS100	2	10	3	10.8	274	7.3	3.3
MAN3-SS100	3	15	4.5	12.8	324	8.3	3.7
MAN4-SS100	4	20	6	14.7	374	9.2	4.2
MAN5-SS100	5	25	7.5	16.7	424	10.1	4.6
MAN6-SS100	6	30	9	18.7	474	11.1	5.0
MAN7-SS100	7	35	10.5	20.6	524	12.0	5.5
MAN8-SS100	8	40	12	22.6	574	13.0	5.9
MAN9-SS100	9	45	13.5	24.6	624	14.0	6.3
MAN10-SS100	10	50	15	26.6	674	14.9	6.7
MAN11-SS100	11	55	16.5	28.5	724	15.8	7.2
MAN12-SS100	12	60	18	30.5	774	16.8	7.6
MAN13-SS100	13	65	19.5	32.5	824	17.8	8.1
MAN14-SS100	14	70	21	34.4	874	18.7	8.5
MAN15-SS100	15	75	22.5	36.4	924	19.7	8.9


MANIFOLD

Caltherm Mega

Our stainless steel manifold kit comes with 1 1/2" connection but it is also available in 1 1/4" connection.

Headers are offered in 14 models (2 to 15 loops) with a maximum flow rate of 30 gallons per minute (GPM).

The integrated flowmeters allow the user to adjust the flow easily in each loop. Circuit isolation valves are also compatible with 24V actuators from Calefactio (#AC24VNC).



TECHNICAL DATA

- Headers with 1 1/4" or 1 1/2" connections
- Made of 304 stainless steel
- Preassembled on wall support for easy installation
- Integrated flowmeters (7.9 LPM / 2 GPM per loop)
- Maximum pressure: 125 psi / 862 kPa
- Maximum temperature: 230°F / 110°C
- Provided with air purger and drain
- Compatible with Calefactio 24 volt actuator (#AC24NC)
- Compatible with ethylene and propylene glycol up to a maximum of 50% concentration
- Possibility to isolate each loop with isolating valve and balancing valve
- 2-way NPT ball valve with integrated thermometer

1 1/4" Connection*	Model#	Loops	Maximum flow		Length (A)		Weight	
			LPM	GPM	in	mm	lb	kg
MAN2-M150SS-BV125	2	15.8	4	11.2	285	8.8	4.0	
MAN3-M150SS-BV125	3	23.7	6	13.2	335	9.9	4.5	
MAN4-M150SS-BV125	4	31.6	8	15.2	385	11.0	5.0	
MAN5-M150SS-BV125	5	39.5	10	17.1	435	12.0	5.5	
MAN6-M150SS-BV125	6	47.4	12	19.1	485	13.1	6.0	
MAN7-M150SS-BV125	7	55.3	14	21.1	535	14.2	6.4	
MAN8-M150SS-BV125	8	63.2	16	23.0	585	15.3	6.9	
MAN9-M150SS-BV125	9	71.1	18	25.0	635	16.3	7.4	
MAN10-M150SS-BV125	10	79	20	27.0	685	17.4	7.9	
MAN11-M150SS-BV125	11	86.9	22	29.0	735	18.5	8.4	
MAN12-M150SS-BV125	12	94.8	24	30.9	785	19.5	8.9	
MAN13-M150SS-BV125	13	102.7	26	32.9	835	20.5	9.3	
MAN14-M150SS-BV125	14	110.6	28	34.9	885	21.6	9.8	
MAN15-M150SS-BV125	15	118.5	30	37	935	22.6	10.2	

1 1/2" Connection*	Model#	Loops	Maximum Flow		Length (A)		Weight	
			LPM	GPM	in	mm	lb	kg
MAN2-M150SS-BV150	2	15.8	4	11.2	285	8.8	4.0	
MAN3-M150SS-BV150	3	23.7	6	13.2	335	9.9	4.5	
MAN4-M150SS-BV150	4	31.6	8	15.2	385	11.0	5.0	
MAN5-M150SS-BV150	5	39.5	10	17.1	435	12.0	5.5	
MAN6-M150SS-BV150	6	47.4	12	19.1	485	13.1	6.0	
MAN7-M150SS-BV150	7	55.3	14	21.1	535	14.2	6.4	
MAN8-M150SS-BV150	8	63.2	16	23.0	585	15.3	6.9	
MAN9-M150SS-BV150	9	71.1	18	25.0	635	16.3	7.4	
MAN10-M150SS-BV150	10	79	20	27.0	685	17.4	7.9	
MAN11-M150SS-BV150	11	86.9	22	29.0	735	18.5	8.4	
MAN12-M150SS-BV150	12	94.8	24	30.9	785	19.5	8.9	
MAN13-M150SS-BV150	13	102.7	26	32.9	835	20.5	9.3	
MAN14-M150SS-BV150	14	110.6	28	34.9	885	21.6	9.8	
MAN15-M150SS-BV150	15	118.5	30	37	935	22.6	10.2	

* Caltherm Mega's body is offered in 1 1/2 in. BV125 suffix means that it is connected to the system through a 1 1/4 in ball valve while suffix BV150 is connected to the system through a 1 1/2 in ball valve.

FITTINGS and Rings

Our compression fittings and our F1960 cold expansion fittings are made of brass, for increased durability.




OUR FITTINGS ARE MADE WITH ACCORDING
TO ASTM F1960 AND ASTM F877.

COMPRESSION FITTINGS

TECHNICAL DATA

- **Material:** Brass
- **O-Ring:** Buna-N
- **Type de connexion:** 3/4" BSPP
- **Maximum temperature:** 200°F (93°C)
- **Maximum pressure:** 160 psi (11 bar)

Model#	Weight	
	lb	kg
FC12	0.16	0.07
FC58	0.18	0.08
FC34	0.33	0.15



FITTINGS AND COLD EXPANSION CRIMP RINGS F1960

The cold expansion ring is made of PEX-a just like our tubing Calpex-R to offer a permanent tightest without welding. Our fittings are made with according to ANSI/NSF 14, ANSI/NSF 61, ASTM F1960 and CSA B137.5.


TECHNICAL DATA

- Use with cold expansion crimp rings F1960
- **Material:** Crosslinked polyethylene (PEX-a)
- **Maximum temperature:** 200°F (93°C)

Model#	Conn.	Weight	
		lb	g
CPR12	1/2"	0.0044	2
CPR58	5/8"	0.0066	3
CPR34	3/4"	0.0088	4.5
CPR1	1"	0.011	5



Cold expansion crimp rings F1960



Cold expansion fittings F1960

TECHNICAL DATA

- **Material:** Brass
- **O-Ring:** Buna-N
- **Type de connexion:** 3/4" BSPP
- **Maximum temperature:** 200°F (93°C)
- **Maximum pressure:** 160 psi (11 bar)

Model#	Weight	
	lb	kg
FF12	0.23	0.10
FF58	0.24	0.11
FF34	0.24	0.11

ELBOWS AND MOUNTING CLIPS

EXCLUSIVE AT CALEFACTIO

Due to our rigid PVC elbows and our polyethylene mounting clips, you'll be organizing your tubing in no time, just like the pros.

ADVANTAGES

- Allows modular and directional installation of elbows
- Offers great flexibility when aligning your pipes
- Quick and easy installation on nailing base
- For a professional look and feel
- Space saving
- No special tools required
- Can be used for residential or commercial projects

ELBOW

TECHNICAL DATA

- Made in PVC
- 1 elbow per package
- Use with PEX-a tubing 1/2" and 5/8"
- Can be installed with Calefactio's mounting clips (#CE-100CLIP)

Model#	Weight	
	lb	kg
CE-100 (1")	0.2	0.09




MOUNTING CLIPS

Unlike the competition, Calefactio's mounting clips allow a modular installation and directional installation. In addition, 90° elbows prevent PEX-a tubing from bending and/or crack under the concrete floor.

TECHNICAL DATA

- Made in polyethylene
- Box of 15 clips, screws included (#8, 1 1/4")
- Can be installed with Calefactio's elbow (#CE-100)

Model#	Weight	
	lb	kg
CE-100CLIP	0.035	0.016



PREASSEMBLED COMPLETE MANIFOLD CABINETS

CAL-PANNEL-PRO


Calefactio's preassembled complete manifold cabinets are factory tested and allow different configurations.

TECHNICAL DATA

- Installation inside walls between 4 in and 6 in deep
- Safety lock
- Screws and safety lock nuts included
- Door, frame and housing made of 18 gauge steel
- Model #MWC52SS made of 18 gauge SS304 stainless steel
- Covered with a white baked paint
- Adjustable door frame

FEATURES

- With or without pump
- With or without actuators
- With or without 3-way valve (0-10 volts or 24 volts floating)



ELECTROTHERMIC ACTUATOR 24V FOR CALEFACTIO MANIFOLDS

When there are multiple thermostats connected to one manifold, then it's essential to use actuators to control the distribution flow in the loops according to the thermostat demands. With this, you will be able to manage the temperature of each zone independently.

TECHNICAL DATA

- **Type of movement:** linear movement
- **Maximum actuator stroke:** 3.5 mm
- **Working stroke on valve:** 2.5 mm
- **Rated voltage:** 24 V (+10% / -15%)
- **Frequency:** 60 Hz
- **Power consumption:** 2.0 W-24 V (continuous duty)
- **Version:** NC (normally closed), 2-wire
- **Time to open/close:** ~ 90-120 seconds
- **Protection degree:** IP54 according to EN 60529
- **Electrical protection class:** Class II
- **Connecting cable:** length 1 m 2 × 2.0 mm²
- **Ambient temperature range:** 0°C up to 50°C during use
- **Storage temperature range:** -25°C up to 60°C
- **Mechanical connection:** threaded ring nut M30 × 1.5



Actuator

Model#	Connection	Weight	
		lb	kg
AC24NC	¾" × ½"	0.44	0.2

CABINET

Model#	Height		Width		Depth	Weight	
	LPM	GPM	in	mm		lb	kg
MWC24	640	25¼	600	24	110 to 150 mm 4¾ to 6 in	23.4	10.6
MWC32	640	25¼	800	32		30.0	13.6
MWC40	640	25¼	1000	40		35.3	16.0
MWC52	640	25¼	1320	52		43.4	19.7
MWC52SS*	640	25¼	1320	52		43.4	19.7



*Door and frame in 18 gage stainless steel (SS304).

ACCESSORIES

Pression Differential By-Pass Valves

Model#	Description	Weight	
		lb	kg
PDBV075N	¾"NPT, adjustable pressure	0.8	0.36
PDBV100	1", fixed pressure	1.4	0.7



Union

Model#	Description	Weight	
		lb	kg
CM150	Coupling manifold	0.38	0.17



Repair Fitting

Model#	Description	Weight	
		lb	kg
CG075	G ¾" Connection	0.11	0.049



Plug

Model#	Description	Weight	
		lb	kg
PLUG-G075	G ¾" Connection	0.08	0.04




PEX Cutter

Model#	Description	Weight	
		lb	kg
CUTTER	For PEX tubing until 1"	0.4	0.2



Zone Controller

Model#	Description	Weight	
		lb	kg
CTR-24V	24V	1.6	0.58



Quebec, Canada

T (450) 951-0818

F (450) 951-2165

CALEFACTIO RADIANT.COM

